



### thermoMETER CTlaserGLASS

*Innovative precision infrared temperature sensor marking the actual spot size on your measurement target at any distance with 5.0µm wavelength for glass targets*

- Measuring range from 100°C to 1650°C
- Accurate glass temperature measurements on flat glass lines, container glass machines, bulb manufacturing, car glass finishing and the production of solar panels
- Cooling and protection accessories for harsh environmental conditions available
- Real mapping of the actual spot size, with automatic laser protection
- Precision optics (45:1 / 70:1) with different models for a specific focus point
- Extreme small measurement spot down to 1mm
- Up to 85°C ambient temperature without cooling
- Fully programmable instrument for enhanced signal processing and I/O control
- Separate controller with easy accessible programming keys and multi colour LCD backlit display

### Optical specifications thermoMETER CTlaserGLASS


□ = smallest spot size (mm)

Standard Focus optics																	
<b>SF45L</b>	<b>45:1</b>	20	20.8	21.7	22.5	23.4	24.2	25	25.9	27	32.5	38.4	50	61.7	73.4		
<b>SF70H</b>	<b>70:1</b>	20	19.6	19.3	19	18.5	18.2	17.8	17.4	17	21.6	26.3	35.5	44.8	54		
distance in mm		0	150	300	450	600	750	900	1050	1200	1350	1500	1800	2100	2400		
Close Focus optics																	
<b>CF1L</b>	<b>45:1</b>	20	9.5	7	1.6	11	26.3	41.7	57	72.6	88.2	104	119.6	135	165	196	227
<b>CF1H</b>	<b>70:1</b>	20	9	6.5	1	10	25	40	55	70	85	100	115	130	160	190	220
<b>CF2L</b>	<b>45:1</b>	20	16	14.5	12	9	3.4	11.2	19	27	35	42.5	50.3	58	73.6	89.2	105
<b>CF2H</b>	<b>70:1</b>	20	15.5	14	11	8	2.2	9.6	17	24.5	42	39.2	47	54	69	84	99
<b>CF3L</b>	<b>45:1</b>	20	17	16.2	14.5	12.3	8.4	4.5	10.7	16.8	23	29	35	41.3	53.5	65.8	78
<b>CF3H</b>	<b>70:1</b>	20	16.9	16	14	11	7.2	2.9	8.7	14.4	20	25.6	31.2	37.3	48.7	60.2	71.6
<b>CF4L</b>	<b>45:1</b>	20	19.2	19	18.6	18	17	15.6	14.5	13.4	12.3	11.1	10	13.4	20	26.7	33.4
<b>CF4H</b>	<b>70:1</b>	20	18.9	18.5	17.8	17	15.5	14	12.5	11	9.5	8	6.5	9.5	15.4	21.2	27.1
distance in mm		0	40	50	70	100	150	200	250	300	350	400	450	500	600	700	800

## Product identification

CTLG - SF45L - C3

Cable length [3m Standard / 8m / 15m]  
 Focus [SF45L/ SF70H / CF1L/H / CF2L/H / CF3L/H / CF4L/H]  
 thermoMETER CTLaserGLASS



Model	CTLG-SF45L-C3	CTLGF-SF45H-C3	CTLG-SF70H-C3	CTLGF-SF45H1-C3
Optical resolution	45:1		70:1	45:1
Temperature range <sup>1</sup>	100 to 1200°C	200 to 1450°C	250 to 1650°C	400 to 1650°C
Spectral range	5.0µm			
System accuracy <sup>2</sup>	±1% or ±1.5°C			
Repeatability <sup>2</sup>	±0.5% or ±0.5°C			
Temperature resolution	0.1°C			
Response time (90% signal)	120ms	10ms	80ms	10ms
Emissivity/gain <sup>1</sup>	0.100 to 1.100			
Transmissivity/gain <sup>1</sup>	0.100 to 1.000			
Signal processing <sup>1</sup>	peak hold, valley hold, average; extended hold function with threshold and hysteresis			
Certificate of calibration	optional			
Outputs/analogue	channel 1 channel 2 optional	0/4 to 20mA, 0 to 5/10V, thermocouple J, K sensor temperature (-20 to 180°C as 0 to 5V or 0 to 10V), alarm output relay: 2 x 60VDC/ 42VAC <sub>eff.</sub> ; 0.4A; optically isolated		
Alarm output		open - collector (24V/ 50mA)		
Outputs/digital	optional	USB, RS232, RS485, CAN, Profibus DP, Ethernet		
Output impedances	current output voltage output	mA max. 500Ω (with 5 to 36VDC) mV min. 100kΩ load impedance; thermocouple 20Ω		
Inputs		programmable functional inputs for external emissivity adjustment, ambient temperature compensation, trigger (reset of hold functions)		
Cable length		3m (standard), 8m, 15m		
Power supply		8 to 36VDC; max. 160mA		
Laser		class II (635nm), 1mW, ON/OFF via controller or software		
Environmental rating		IP 65 (NEMA-4)		
Ambient temperature		sensor: -20°C to 85°C (50°C if Laser is ON) controller: 0°C to 85°C		
Storage temperature		sensor: -40°C to 85°C controller: -40°C to 85°C		
Relative humidity		10 to 95%, non condensing		
Vibration	sensor	IEC 68-2-6: 3G, 11 to 200Hz, any axis		
Shock	sensor	IEC 68-2-27: 50G, 11ms, any axis		
Weight		sensor: 600g; controller: 420g		

<sup>1</sup> adjustable via controller or software<sup>2</sup> ± ambient temperature: 23 ±5°C; whichever is greater

## Accessories page 22 - 23

- ▶ Mounting bracket
- ▶ Air purge collar
- ▶ Rail mount adapter for controller
- ▶ Water cooled housing
- ▶ Interface kit
- ▶ Software CompactConnect
- ▶ Certificate of calibration



**LASER RADIATION**  
 DO NOT STARE IN THE BEAM  
 CLASS 2 LASER  
 EN60825-1:2002  
 P≤1mW; λ=630-650nm